

LAU3200R/LAD3200R/LAV3200R

KEY FEATURES

- Full HD (1080p) Image
- Reliable Day & Night function by ICR
- ATC (Automatic Tone Control)
- Image Transmission through BNC Cable
- IP66 Support

SPECIFICATIONS



Features		LAU3200R	LAD3200R	LAV3200R
Camera	Image Sensor	CMOS	CMOS	CMOS
	Lens	4 mm F2.1	4 mm F2.1	2.8-12 mm F1.4
	Min. Illumination	0 lux @ IR LED on	0 lux @ IR LED on	0 lux @ IR LED on
	Day / Night	ICR (Auto)	ICR (Auto)	ICR (Auto)
	WDR	Digital (Automatic Tone Control)	Digital (Automatic Tone Control)	Digital (Automatic Tone Control)
	Electronic Shutter	Auto	Auto	Auto
	3D-DNR	Auto	Auto	Auto
	Gain Control	Auto	Auto	Auto
	IR LEDs	30	24	28
	IR Distance	20 m	20 m	30 m
Video	Focus	Manual	Manual	Manual
	Video Format	AHD	AHD	AHD
	Max. Frame Rate	30 fps @ 1920 x 1080 (NTSC) 25 fps @ 1920 x 1080 (PAL)	30 fps @ 1920 x 1080 (NTSC) 25 fps @ 1920 x 1080 (PAL)	30 fps @ 1920 x 1080 (NTSC) 25 fps @ 1920 x 1080 (PAL)
	Synchronization	Internal	Internal	Internal
	Max. Transmission Distance	500m (75Ω-5C)	500m (75Ω-5C)	500m (75Ω-5C)
	Interface	BNC	BNC	BNC
General	Power Source	DC12V	DC12V	DC12V
	Max. Power Consumption	4.2 W	4.2 W	4.2 W
	Operating Temperature / Humidity	-10 °C ~ 55 °C / 0% ~ 80%RH	-10 °C ~ 55 °C / 0% ~ 80%RH	-10 °C ~ 55 °C / 0% ~ 80%RH
	Standard Approvals	CE, FCC, LVD	CE, FCC, LVD	CE, FCC, LVD
	Color / Material	White / Diecasting	White / Diecasting	White / Diecasting
	Ingress Protection	IP66	IP66	IK10, IP66
	Dimension (Ø x H)	70.3 x 66.0 x 172.8 mm	Ø93 x 68 mm	Ø147 x 112 mm
	Weight	340 g	330 g	820 g