

LNU5460R/LNU7260R

Motorized Vari-focal IP Bullet Camera

SPECIFICATIONS



Features	LNU5460R	LNU7260R		
Camera	Image Sensor	CMOS	CMOS	
	Lens	3.3-10mm, Motorized Lens	3.3-10mm, Motorized Lens	
	Min. Illumination	Color 0.5 lux @ F1.4 (AGC on) B/W 0 lux @ IR LED on	Color 0.03 lux @ F1.4 (AGC ON) B/W 0 lux @ IR LED on	
	Day / Night	Dual ICR	Dual ICR	
	WDR	Digital WDR	Digital WDR	
	IR LEDs	30 IR LED + 27 LED	30 IR LED + 27 LED	
	IR Distance	30 m	30 m	
	Focus	Auto	Auto	
	Image Setting	Configurable Brightness, Saturation, Contrast, Flip Mode, HLC, Smart Defog, Corridor, EIS	Configurable Brightness, Saturation, Contrast, Flip Mode, HLC, Smart Defog, Corridor, EIS	
	Video/Audio	Video Compression	H.265, H.264 HP/MP/BP, M-JPEG	H.265, H.264 HP/MP/BP, M-JPEG
Resolution		60Hz 1440p@25fps, QXGA@25fps, 1080p@30fps, 960p@30fps, 720p@30fps 50Hz 1440p@25fps, QXGA@25fps, 1080p@25fps, 960p@25fps, 720p@25fps	60Hz 1080p@30fps, 960p@30fps, 720p@60fps 50Hz 1080p@25fps, 960p@25fps, 720p@50fps	
Max. Frame Rate		2048x1536@30fps, 1280x720@60fps	1920x1080@30fps, 1280x720@60fps	
Multi-Streaming		3	3	
ROI (Region of Interest)		4 zones	4 zones	
Privacy Mask		Yes (Up to 4)	Yes (Up to 4)	
Motion Detection		Yes	Yes	
Video Analytics		Tripwire/Perimeter/Missing&Foreign object/Crowd/Loitering/Fast Moving/Parking/Off-position/Blurred Image/Audio Offline/Screaming Detection	Tripwire/Perimeter/Missing&Foreign object/Crowd/Loitering/Fast Moving/Parking/Off-position/Blurred Image/Audio Offline/Screaming Detection	
Streaming on Motion		Yes	Yes	
Text Overlay		Yes	Yes	
Audio Compression		G.711A/G.711U/ADPCM/AAC	G.711/G.726/ADPCM/AAC	
Two-way Audio		Yes	Yes	
Audio Detection		Yes	Yes	
Event		Event Trigger	Motion Detection/IP Conflict/MAC Conflict/Port Alarm	Motion Detection/IP Conflict/MAC Conflict/Port Alarm
		Event Notification	Relay out, Email, FTP	Relay out, Email, FTP
	Pre/Post Event Buffering	Yes	Yes	
Interface	Analog Video Out	1 BNC Out	1 BNC Out	
	Audio In / Out	1 In / 1 Out	1 In / 1 Out	
	Alarm In / Out	2 In / 1 Out	2 In / 1 Out	
	Storage	Micro SD (Up to 128 GB)	Micro SD (Up to 128 GB)	
Network	Ethernet	RJ-45 10/100BASE-T	RJ-45 10/100BASE-T	
	Security	Password protection, IP filter	Password protection, IP filter	
	Open Protocol	ONVIF (Profile S)	ONVIF (Profile S)	
	Protocol	IPv4/IPv6, HTTP, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, TCP, UDP, DHCP, PPPoE	IPv4/IPv6, HTTP, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, TCP, UDP, DHCP, PPPoE	
	Web Viewer	IE8, IE10, IE11, Chrome42 under version, Firefox 3.5+	IE8, IE10, IE11, Chrome42 under version, Firefox 3.5+	
	Video Management Software	Mobile App (iPhone, iPad, Android)	Mobile App (iPhone, iPad, Android)	
	Max. Connections	4 Level/8 Users	4 Level/8 Users	
	Power Source	DC12V, AC24V, POE	DC12V, AC24V, POE	
General	Max. Power Consumption	12.5W	12.5W	
	Max. Input Current	890mA (AC24V), 980mA (DC12V), 260mA (PoE)	890mA (AC24V), 980mA (DC12V), 260mA (PoE)	
	Operating Temperature / Humidity	-30°C ~ 60°C / 0% ~ 95%RH	-30°C ~ 60°C / 0% ~ 95%RH	
	Standard Approvals	CCC, Police (China), KC, LVD, CE	CCC, Police (China), KC, LVD, CE	
	Language	Korean, Chinese, Japanese, English, Turkish, Spanish	Korean, Chinese, Japanese, English, Turkish, Spanish	
	Color / Material	Black & White / Diecasting	Black & White / Diecasting	
	Ingress Protection	IK10, IP66	IK10, IP66	
	Dimension (Ø x H)	97.1mm x 89.4mm x 311.8mm	97.1mm x 89.4mm x 311.8mm	
	Weight	1.3kg (Camera Only)	1.3kg (Camera Only)	

KEY FEATURES

- Multi-codec (H.265, H.264, H.264, H.264, H.264, H.264) Streaming
- Intelligent Video Analysis
- PoE (Power over Ethernet) Support
- 3 Power (AV 24V, DC 12V, PoE) Support
- Audio / Alarm Support
- Motorized Lens Support
- IR Distance 30m