

LNV5460R/LNV7260R

Motorized Vari-focal IP Dome Camera

SPECIFICATIONS



Features	LNV5460R	LNV7260R		
Camera	Image Sensor	CMOS	CMOS	
	Lens	3.3-10mm, Motorized Lens	3.3-10mm, Motorized Lens	
	Min. Illumination	Color 0.5 lux @ F1.4 (AGC on) B/W 0 lux @ IR LED on	Color 0.03 lux @ F1.4 (AGC ON) B/W 0 lux @ IR LED on	
	Day / Night	Dual ICR	Dual ICR	
	WDR	Digital WDR	Digital WDR	
	IR LEDs	32	32	
	IR Distance	30 m	30 m	
	Focus	Auto	Auto	
	Image Setting	Configurable Brightness, Saturation, Contrast, Flip Mode, HLC, Smart Defog, Corridor, EIS	Configurable Brightness, Saturation, Contrast, Flip Mode, HLC, Smart Defog, Corridor, EIS	
	Video/ Audio	Video Compression	H.265, H.264 HP/MP/BP, M-JPEG	H.265, H.264 HP/MP/BP, M-JPEG
Resolution		60Hz 1440p@25fps, QXGA@25fps, 1080p@30fps, 960p@30fps, 720p@30fps 50Hz 1440p@25fps, QXGA@25fps, 1080p@25fps, 960p@25fps, 720p@25fps	60Hz 1080p@30fps, 960p@30fps, 720p@60fps 50Hz 1080p@25fps, 960p@25fps, 720p@50fps	
Max. Frame Rate		2048x1536@30fps, 1280x720@60fps	1920x1080@30fps, 1280x720@60fps	
Multi-Streaming		3	3	
ROI (Region of Interest)		8	8	
Privacy Mask		Yes (Up to 4)	Yes (Up to 4)	
Motion Detection		Yes	Yes	
Video Analytics		Tripwire/Perimeter/Missing&Foreign object/Crowd/Loitering/Fast Moving/Parking/Off-position/Blurred Image/Audio Offline/Screaming Detection	Tripwire/Perimeter/Missing&Foreign object/Crowd/Loitering/Fast Moving/Parking/Off-position/Blurred Image/Audio Offline/Screaming Detection	
Streaming on Motion		Yes	Yes	
Text Overlay		Yes	Yes	
Event	Audio Compression	G.711A/G.711U/ADPCM/AAC	G.711A/G.711U/ADPCM/AAC	
	Two-way Audio	Yes	Yes	
	Audio Detection	Yes	Yes	
	Event Trigger	Motion Detection/IP Conflict/MAC Conflict/Port Alarm	Motion Detection/IP Conflict/MAC Conflict/Port Alarm	
	Event Notification	Relay out, Email, FTP	Relay out, Email, FTP	
	Pre/Post Event Buffering	Yes	Yes	
	Interface	Analog Video Out	1 BNC Out	1 BNC Out
		Audio In / Out	1 In / 1 Out	1 In / 1 Out
		Alarm In / Out	2 In / 1 Out	2 In / 1 Out
	Network	Storage	Micro SD (Up to 128 GB)	Micro SD (Up to 128 GB)
Ethernet		RJ-45 10/100BASE-T	RJ-45 10/100BASE-T	
Security		Password protection, IP filter	Password protection, IP filter	
Open Protocol		ONVIF (Profile S)	ONVIF (Profile S)	
Protocol		IPv4/IPv6, HTTP, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, TCP, UDP, DHCP, PPPoE	IPv4/IPv6, HTTP, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, TCP, UDP, DHCP, PPPoE	
Web Viewer		IE8, IE10, IE11, Chrome42 under version, Firefox 3.5+	IE8, IE10, IE11, Chrome42 under version, Firefox 3.5+	
Video Management Software		Mobile App (iPhone, iPad, Android)	Mobile App (iPhone, iPad, Android)	
Max. Connections		4 Level/8 Users	4 Level/8 Users	
General		Power Source	DC12V, AC24V, POE	DC12V, AC24V, POE
		Max. Power Consumption	11W	11W
	Max. Input Current	810mA (AC24V), 880mA (DC12V), 230mA (PoE)	810mA (AC24V), 880mA (DC12V), 230mA (PoE)	
	Operating Temperature / Humidity	-30°C ~ 60°C / 0% ~ 95%RH	-30°C ~ 60°C / 0% ~ 95%RH	
	Standard Approvals	KC, LVD, CE	KC, LVD, CE	
	Language	Korean, Chinese, Japanese, English, Turkish, Spanish	Korean, Chinese, Japanese, English, Turkish, Spanish	
	Color / Material	White / Diecasting	White / Diecasting	
	Ingress Protection	IK10, IP66	IK10, IP66	
	3-Axis	Manual	Manual	
	Dimension (Ø x H)	150mm x 122mm	150mm x 122mm	
Weight	0.96kg (Camera Only)	0.96kg (Camera Only)		

KEY FEATURES

- Multi-codec (H.265, H.264, HJPEG) Streaming
- Intelligent Video Analysis
- PoE (Power over Ethernet) Support
- 3 Power (AV 24V, DC 12V, PoE) Support
- Audio / Alarm Support
- Motorized Lens Support
- IR Distance 30m

DIMENSION (Unit : mm)

