

RNOE-B501A

2MP Box Camera

SPECIFICATIONS

| Features | RNOE-B501A | |
|-------------------------|----------------------------------|--|
| Camera | Image Sensor | 1/2.7" CMOS |
| | Mount Type | C/CS |
| | Min. Illumination | Color: 0.08 Lux(F1.2,AGC ON) B/W: 0.06 Lux(F1.2,AGC ON) ; |
| | Day / Night | Dual ICR |
| | WDR | Digital |
| | Focus | ABF |
| | Image Setting | Configurable Brightness, Saturation, Contrast, Flip Mode, HLC, Smart Defog, Corridor, EIS |
| Video/ Audio | Video Compression | H.265, H.264 HP/MP/BP, M-JPEG |
| | Resolution | 60Hz: 30fps(1920×1080) 50Hz: 25fps(1920×1080) |
| | Max. Frame Rate | 1080p@30fps |
| | Multi-Streaming | 3 |
| | ROI (Region of Interest) | 8 zones |
| | Privacy Mask | Yes (Up to 4) |
| | Motion Detection | Yes |
| | Video Analytics | Tripwire/Perimeter Missing&Foreign object/Crowd/Loitering/Fast Moving/Parking/Off-position/Blurred Image/Audio Offline/Screaming Detection |
| | Streaming on Motion | Yes |
| | Text Overlay | Yes |
| Event | Audio Compression | G.711A/G.711U/ADPCM/AAC |
| | Two-way Audio | Yes (同源无差别) |
| | Audio Detection | Yes |
| | Event Trigger | Motion Detection/IP Conflict/MAC Conflict/Port Alarm |
| | Event Notification | Relay out, Email, FTP |
| Interface | Pre/Post Event Buffering | no |
| | Analog Video Out | 1 BNC Out |
| | Audio In / Out | 1 In / 1 Out |
| | Alarm In / Out | 2 In / 1 Out |
| | RS-485 | Yes |
| Network | Storage | 1XSD(up to 512G) |
| | Ethernet | RJ-45 10/100BASE-T |
| | Security | no |
| | Open Protocol | ONVIF (Profile S) |
| | Protocol | TCP/UDP/HTTP/MULTICAST/UPnP/DHCP/PPPoE/DDNS/NFS/FTP/NTP/RTP/RTSP/IPv6/SNMP/SMTP/802.1X/QoS/HTTPS(customize) |
| | Web Viewer | IE8, IE10, IE11, Chrome42 under version,Firefox3.5+ |
| | Video Management Software | Mobile App (iPhone, iPad, Android) |
| General | Max. Connections | 4 Level/8 Users |
| | Power Source | DC12V±10%、AC24V±15%、POE |
| | Max. Power Consumption | 6 W |
| | Max. Input Current | - |
| | Operating Temperature / Humidity | -35° C - 65° C / 0% - 95%RH |
| | Standard Approvals | Police (China) |
| | Language | Korean, Chinese, Japanese, English, Arabic, Turkish, Spanish |
| | Color / Material | Black & White/ Diecasting |
| Dimension (W x H x D) | 170.6mm×76mm×64mm | |
| Weight | 0.9kg (Camera Only) | |

KEY FEATURES

- Multi-codec (H.265, H.264, HJPEG) Streaming
- Intelligent Video Analysis
- PoE (Power over Ethernet) Support
- 3 Power (AC 14V, DC 12V, PoE) Support
- Audio / Alarm Support
- ABF Support