

RNZE-B501A

Outdoor PTZ Camera



SPECIFICATIONS

	Features	RNZE-B501A
Camera	Image Sensor	1/2.8" SNOY Exmor CMOS
	Lens	x33, 4.6-152mm , F1.6-F4.8
	Min. Illumination	Color 0.03Lux @ (F1.6 , 50 IRE , ICR off) B/W 0.02Lux @F1.6 , 50 IRE , ICR on)
	Day / Night	Dual ICR
	WDR	Digital WDR
	IR Distance	150m
	Image Setting	Backlight compensation, HSBL, 2D+3D Noise reduction, Exposure control, Sens-up control, AGC, White balance, EIS, Sharpness, Auto digital zoom, Defog
PTZ	Optical Zoom	x33
	Panning Range & Speed	0° -360° , Max. 240° /sec
	Tilting Range & Speed	-16° - 90° , Max. 180° /sec
	Auto Panning	8
	Preset/ID	500
	Group touring	8
	Pattern	8
Video/Audio	Video Compression	H.265, H.264 High Profile, MJPEG
	Resolution	60Hz 1080p@30fps , 960p@30fps , 720p@60fps 50Hz 1080p@25fps , 960p@25fps , 720p@50fps
	Max. Frame Rate	1280x720@50/60fps
	Multi-Streaming	3
	ROI (Region of Interest)	4 zones
	Privacy Mask	Yes (up to 4)
	Motion Detection	Yes
	Video Analytics	yes
	Text Overlay	yes
	Audio Compression	G.711A, G.711U, AAC, ADPCM
	Two-way Audio	yes
Event	Event Trigger	Motion detection, Alarm input , IP Conflict , MAC Conflict , Port Alarm
	Event Notification	Relay out, Email, FTP, Go to Preset
	Pre/Post Event Buffering	Yes
Interface	Audio In / Out	1 In / 1 Out
	Alarm In / Out	1 In / 1 Out
	Storage	Micro SD , Up to 128GB
Network	Ethernet	RJ-45 10/100BASE-T
	Security	Password protection, IP filter
	Open Protocol	ONVIF (Profile S)
	Protocol	TCP/UDP/HTTP/MULTICAST/UPnP/DHCP/PPPoE/DDNS/NFS/FTP/NTP/RTP/RTSP/IP v6/SNMP/SMTP
	Web Viewer	IE8, IE10, IE11 , Chrome42 under version, Firefox3.5+
	Video Management Software	Mobile App (iPhone, iPad, Android)
	Max. Connections	4Level / 8 Users
General	Power Source	AC24V
	Max. Power Consumption	27W (2,200mA)
	Operating Temperature / Humidity	-40° C - 60° C / 0% - 95%RH
	Standard Approvals	KC, LVD, CE
	Language	Japanese, Korean, Chinese, English, Turkish, Spanish
	Color / Material	White , BLack/ Diecasting
	Ingress Protection	IP66
	Dimension (Ø xH)	Ø223 x 372 mm
	Weight	5.1kg (Camera Only)

KEY FEATURES

- Multi-codec (H.265, H.264, HJPEG) Streaming
- Intelligent Video Analysis
- 33x optical zoom Support
- Power AC 24V Support
- Audio / Alarm Support
- IR Distance 150m
- 360° Pan, 90° Tilt Support